

CLEVIS AND INTERNAL THREAD END RIGHT-HAND SWAGED FOR ROPE Ø 3 - 8 MM

30812

TECHNICAL SPECIFICATION



828INDUSTRIES.COM

Jakob Rope Systems · Architectural Cables & Fittings

Clevis with internal thread swaged by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 9 sizes, article no. 30812-0300-01 to 30812-0800-01.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30812
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	STATUS	Ø	A	B	E	F	G	H	Ø D1	Ø D2	-	+	KG
30812-0300-01	Phased out	3	M 5	94	6	12	7.5	12.5	5	7	8	5	0.0320
30812-0300-02	Phased out	3	M 5	110	6	12	7.5	12.5	5	7	15	13	0.0400
30812-0400-01	Phased out	4	M 6	95	6	12	7.5	12.5	5	8	8	3	0.0370
30812-0400-02	Phased out	4	M 6	120	6	12	7.5	12.5	5	8	15	11	0.0450
30812-0500-01	Phased out	5	M 6	105	6	12	7.5	12.5	5	8	8	3	0.0350
30812-0500-02	Phased out	5	M 6	128	6	12	7.5	12.5	5	8	15	11	0.0440
30812-0600-01	Phased out	6	M 8	125	7	13	10	14.5	6	10	10	3	0.0670
30812-0600-02	Phased out	6	M 8	162	7	13	10	14.5	6	10	25	13	0.0840
30812-0800-01	Phased out	8	M 10	204	9	15	11	18	8	13	30	10	0.1860

NOTES

- The screw-in depth of the thread must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.
- Suitable for the circular wire strand ropes of the 10820 and 10830 series.
- The assembly with open spiral strands of the 10810 series is only possible with diameters 2 - 6 mm.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.