

CLEVIS AND INTERNAL THREAD END SWIVEL SWAGED

30823

TECHNICAL SPECIFICATION

Clevis with internal thread swaged by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 8 sizes, article no. 30823-0300-01 to 30823-0600-02.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30823
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	STATUS	Ø	A	B	E	F	G	H	Ø D1	Ø D2	SW	-	+	KG
30823-0300-01	Phased out	3	M5	122	6	12	7.5	12.5	5	10	8	10	3	0.0580
30823-0300-02	Phased out	3	M5	139	6	12	7.5	12.5	5	10	8	15	13	0.0650
30823-0400-01	Phased out	4	M6	121	6	12	7.5	12.5	5	10	8	8	3	0.0540
30823-0400-02	Phased out	4	M6	146	6	12	7.5	12.5	5	10	8	15	11	0.0630
30823-0500-01	Phased out	5	M6	143	6	12	7.5	12.5	5	13	11	8	3	0.0950
30823-0500-02	Phased out	5	M6	167	6	12	7.5	12.5	5	13	11	15	11	0.1060
30823-0600-01	Phased out	6	M8	152	7	13	10	14.5	6	13	11	10	3	0.1070
30823-0600-02	Phased out	6	M8	189	7	13	10	14.5	6	13	11	25	13	0.1240

NOTES

- The clevis and rope can rotate freely. The rope can be tensioned by using right-hand threads on both sides.
- The functionality is ensured only by using circular wire strand ropes of the 10820 and 10830 series.
- The screw-in depth of the thread must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tension)

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.