

CLEVIS CLASSIC AND INTERNAL THREAD-END RIGHT-HAND SWAGED FOR ROPE Ø 3 - 8 MM

30932

TECHNICAL SPECIFICATION

Clevis with internal thread swaged by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 9 sizes, article no. 30932-0300-01 to 30932-0800-01.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30932
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B	E	F	G	H	Ø D1	Ø D2	F RD KN ETA	-	+	KG
30932-0300-01	3	M5	90	7	10	8	13	5	7		8	5	0.0330
30932-0300-02	3	M5	108	7	10	8	13	5	7		15	13	0.0370
30932-0400-01	4	M6	93	7	10	8	13	5	8	5.2	8	3	0.0400
30932-0400-02	4	M6	118	7	10	8	13	5	8	5.2	15	11	0.0480
30932-0500-01	5	M6	101	7	10	8	13	5	8	8.1	8	3	0.0400
30932-0500-02	5	M6	126	7	10	8	13	5	8	8.1	15	11	0.0480
30932-0600-01	6	M8	129	13	16	13	22	8	10	11.6	10	3	0.1020
30932-0600-02	6	M8	166	13	16	13	22	8	10	11.6	25	13	0.1190
30932-0800-01	8	M10	210	15	20	13	25	10	13	20.7	30	10	0.2260

NOTES

- Suitable for the circular wire strand ropes of the 10820 and 10830 series.
- The assembly with open spiral strand ropes of the 10810 series is only possible with diameters 2 - 6 mm.
- The screw-in depth of the thread must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The design resistance FRd (kN) according to ETA refers to use with circular wire strand ropes of construction 6×19+WC (product group 10830). When used with other rope constructions, the value may increase or decrease.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.