

HEAVY DUTY REBAR ADAPTORS

TECHNICAL SPECIFICATION



828INDUSTRIES.COM

Hydrajaws · Pull-out & Load Testers

Wedge-and-barrel grips for pull-testing post-installed rebar: 6-22mm with the M2008 and 24-50mm with the hydraulic hollow cylinder testers.

Wedge-and-barrel grips for pull-testing post-installed rebar: 6-22mm with the M2008 and 24-50mm with the hydraulic hollow cylinder testers.

SUPPLIED BY 828

828 Cable System is the authorized Hydrajaws distributor in the Philippines. We supply the testers with their calibration certificates, can train your team to use them, and can carry out on-site pull-out testing for you.



SPECIFICATIONS

Brand	Hydrajaws
Category	Pull-out & Load Testers
Sizes with M2008	6-22mm
Sizes with hydraulic testers	24, 25, 26, 28, 32, 35, 40, 50mm
Type	Wedge and barrel

ARTICLE NUMBERS

OPTION	DETAILS
T6 (6mm)	—
T8 (8mm)	5/16"
T10 (10mm)	7/16"
T12 (12mm)	1/2"
T14 (14mm)	—
T16 (16mm)	5/8"
T18 (18mm)	—
T20 (20mm)	3/4"
T22 (22mm)	—
T24 (24mm)	hydraulic tester
T25 (25mm)	hydraulic tester
T26 (26mm)	hydraulic tester
T28 (28mm)	hydraulic tester
T32 (32mm)	hydraulic tester
T35 (35mm)	hydraulic tester
T40 (40mm)	hydraulic tester
T50 (50mm)	hydraulic tester

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.