

M2000 SAFETY HARNESS EYE BOLT TESTER KIT

TECHNICAL SPECIFICATION

25kN pull tester kit set up for testing safety harness anchor eyebolts and ringbolts in situ. Intended for periodic inspection of anchor devices under BS 7883 / BS EN 795.

25kN pull tester kit set up for testing safety harness anchor eyebolts and ringbolts in situ. Intended for periodic inspection of anchor devices under BS 7883 / BS EN 795.

IN THE KIT

- M2000 tester (pre-assembled)
- 2020 three-legged load spreading bridge
- Turning handle
- M12 ringbolt adaptor clevis
- M12 locking adaptor
- Gauge (digital or analogue)
- Red protective carry case
- Operating instructions



SUPPLIED BY 828

828 Cable System is the authorized Hydrajaws distributor in the Philippines. We supply the testers with their calibration certificates, can train your team to use them, and can carry out on-site pull-out testing for you.

SPECIFICATIONS

Brand	Hydrajaws
Category	Pull-out & Load Testers
Max tensile load	25kN (5620lbf)
Stroke	Up to 50mm
Gauge	0-25kN dual-scale rechargeable digital gauge (detachable); analogue option
Bridge	2020 three-legged load spreading bridge; 15mm fine adjustment
Turning handle	Integrated 22mm (7/8") nut
Adaptor sizes	M12 ringbolt clevis; M12 locking adaptor
Software	Hydrajaws Verify PRO App (with digital gauge)
Standards referenced	BS EN 795; BS 7883:2019
Calibration	Hydrajaws gauge calibration certificate, valid 12 months

ARTICLE NUMBERS

OPTION	DETAILS
Digital gauge	0-25kN
Analogue gauge	0-25kN

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.