

M2000 SCAFFOLD TIE TESTER KIT

TECHNICAL SPECIFICATION

25kN pull tester kit configured for proof-testing scaffold tie anchors (ringbolts and M16 tie fixings). Set up to follow NASC TG4 scaffold anchorage guidance.

25kN pull tester kit configured for proof-testing scaffold tie anchors (ringbolts and M16 tie fixings). Set up to follow NASC TG4 scaffold anchorage guidance.

IN THE KIT

- Three-legged load spreading bridge
- Turning handle with 22mm integrated nut
- Dual-scale gauge (digital or analogue)
- M12 ringbolt adaptor clevis
- Bolt tester adaptor with M12 locking adaptor
- M16 threaded stud adaptor
- M16 hexagon set screw
- M16 threaded stud
- Protective carry case
- Operating instructions
- Gauge calibration certificate

SUPPLIED BY 828

828 Cable System is the authorized Hydrajaws distributor in the Philippines. We supply the testers with their calibration certificates, can train your team to use them, and can carry out on-site pull-out testing for you.



SPECIFICATIONS

Brand	Hydrajaws
Category	Pull-out & Load Testers
Max tensile load	25kN (5620lbf)
Stroke	Up to 50mm
Gauge	0-25kN dual-scale rechargeable digital gauge (detachable); analogue option
Bridge	Three-legged, height-adjustable, 4 pin positions, swivel feet, 15mm fine adjustment
Turning handle	Integrated 22mm (7/8") nut
Adaptor sizes	M12 ringbolt clevis; M16 threaded stud; M12 locking adaptor
Software	Hydrajaws Verify PRO App (with digital gauge)
Standards referenced	NASC TG4 (Anchorage Systems for Scaffolding; page cites TG4:25 and TG4:19)
Calibration	Hydrajaws gauge calibration certificate, valid 12 months

ARTICLE NUMBERS

OPTION	DETAILS
Digital gauge	0-25kN
Analogue gauge	0-25kN

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.