

M35+ DUAL LOAD CAPACITY DIGITAL PULL TESTER

TECHNICAL SPECIFICATION

Lightweight titanium modular digital pull tester rated 35kN on its standard bridge and up to 65kN with optional medium/large bridges. Packed in a rucksack with a full adaptor set; the platform for Hydrajaws' lifeline, shear, davit and in-line add-ons.

Lightweight titanium modular digital pull tester rated 35kN on its standard bridge and up to 65kN with optional medium/large bridges. Packed in a rucksack with a full adaptor set; the platform for Hydrajaws' lifeline, shear, davit and in-line add-ons.

IN THE KIT

- M35+ tester with standard bridge and digital gauge
- Bolt test adaptor
- 20mm and 24mm clevis forks
- Slotted button adaptors 6.5, 8.5, 10.5, 13, 16.5mm
- Threaded button adaptors M6, M8, M10, M12, M16, M20 (imperial: 1/4", 5/16", 3/8", 1/2", 5/8", 3/4" UNC)
- Rugged rucksack
- Full-colour user manual
- Gauge calibration certificate



SUPPLIED BY 828

828 Cable System is the authorized Hydrajaws distributor in the Philippines. We supply the testers with their calibration certificates, can train your team to use them, and can carry out on-site pull-out testing for you.

SPECIFICATIONS

Brand	Hydrajaws
Category	Pull-out & Load Testers
Capacity (standard bridge)	35kN / 7868lbf (3.5 t)
Capacity (dual bridge)	65kN / 14,613lbf (6.5 t) with optional bridges
Gauge	Dual-scale rechargeable digital
Construction	Titanium, lightweight
Optional bridges	Medium 210mm span SWL 65kN; Large 310mm span SWL 65kN; leg extensions +96mm
Metric adaptors	Bolt test adaptor; 20mm & 24mm clevis forks; slotted 6.5, 8.5, 10.5, 13, 16.5mm; threaded M6-M20
Imperial adaptors	Bolt test adaptor; 20mm & 24mm clevis forks; slotted 6.5-16.5mm; threaded 1/4"-3/4" UNC
Software	Hydrajaws Verify PRO App; includes 2-hour training course
Standards referenced	BS 8539; BS 7883:2019; BS EN 795:2012; BS 8610; NASC TG4:19; AEFAC-TN05
Calibration	Hydrajaws gauge calibration certificate, valid 12 months

ARTICLE NUMBERS

OPTION	DETAILS
Metric Standard Bridge	35kN
Metric Dual Bridge	65kN
Imperial Standard Bridge	7868lbf
Imperial Dual Bridge	14,613lbf

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.