

TENSIONING SCREW ASSEMBLED WITH INTERNAL THREAD ENDS SWAGED FOR ROPE Ø 2 - 8 MM

30816

TECHNICAL SPECIFICATION

Turnbuckles assembled by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 10 sizes, article no. 30816-0200-01 to 30816-0800-01.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30816
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	Ø D	SW	-	+	KG
30816-0200-01	2	M4	103	38	6	4	14	4	0.0170
30816-0300-01	3	M5	139	55	7	5	16	10	0.0320
30816-0300-02	3	M5	183	70	7	5	30	26	0.0490
30816-0400-01	4	M6	145	57	8	6	16	6	0.0480
30816-0400-02	4	M6	191	73	8	6	30	22	0.0650
30816-0500-01	5	M6	161	65	8	6	16	6	0.0460
30816-0500-02	5	M6	207	81	8	6	30	22	0.0670
30816-0600-01	6	M8	207	83	10	8	20	8	0.0940
30816-0600-02	6	M8	288	108	10	8	50	20	0.1240
30816-0800-01	8	M10	376	140	13	10	70	20	0.3020

NOTES

- Assembly including both internal threads pressed.
- The screw-in depth of the threads must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.