

TURNBUCKLE WITH CLEVIS CLASSIC SWAGED FOR ROPE Ø 2 - 12 MM

30970

TECHNICAL SPECIFICATION

Clevis with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 9 sizes, article no. 30970-0200 to 30970-1200.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30970
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	E	F	G	H	Ø D	F_RD KN ETA	-	+	KG
30970-0200	2	M5	176	80	7	10	8	13	5	1.2	34	26	0.0480
30970-0300	3	M6	205	92	7	10	8	13	5	2.7	44	22	0.0750
30970-0400	4	M6	215	92	11	15	10	18	7	4.8	44	22	0.0990
30970-0400-1	4	M8	237	112	13	16	13	22	8	4.8	52	26	0.1840
30970-0500	5	M8	243	112	13	16	13	22	8	7.5	51	26	0.1830
30970-0600	6	M10	275	120	15	20	13	25	10	10.9	54	20	0.2800
30970-0800	8	M12	353	150	19	24	16	32	12	19.3	70	34	0.5390
30970-1000	10	M16	458	190	23	32	22	38	14	30.2	84	42	1.1150
30970-1200	12	M20	549	220	30	38	22	50	20	43.5	98	50	2.0470

NOTES

- The screw-in depth of the threads must be at least 1,5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.
- Suitable for circular wire strand ropes of product groups 10820 and 10830.
- Assembly with open spiral ropes of product group 10810 is only possible for diameters from 2 to 6 mm.
- The design resistance FRd (kN) according to ETA refers to use with circular wire strand ropes of construction 6×19+WC (product group 10830). When using the 6×7+WC rope construction (product group 10820), the resistance value increases.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.