

TURNBUCKLE WITH CLEVIS CLASSIC UNIVISS ROUND SWAGED

30970

TECHNICAL SPECIFICATION

Clevis with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 6 sizes, article no. 30970-0500-10 to 30970-0800-11.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30970
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	E	F	G	H	Ø D	-	+	KG
30970-0500-10	5	M5	149	80	7	10	8	13	5	22	16	0.0450
30970-0500-11	5	M5	180	80	7	10	8	13	5	34	26	0.0500
30970-0600-10	6	M6	168	92	7	10	8	13	5	20	12	0.0670
30970-0600-11	6	M6	205	92	7	10	8	13	5	44	22	0.0780
30970-0800-10	8	M8	211	112	13	16	13	22	8	17	6	0.1400
30970-0800-11	8	M8	243	112	13	16	13	22	8	51	26	0.1610

NOTES

- Univiss thread-end with round shaft.
- Only in use with circular wire strand ropes of the 10820 series.
- The minimum free rope length between the fittings is 95 mm.
- The screw-in depth of the threads must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.