

TURNBUCKLE WITH CLEVIS LT1 SELF-ASSEMBLY

30822

TECHNICAL SPECIFICATION



828INDUSTRIES.COM

Jakob Rope Systems · Architectural Cables & Fittings

Clevis with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 10 sizes, article no. 30822-0200 to 30822-1200.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30822
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	E	F	G	H	Ø D	F_RD KN	-	+	KG
30822-0200	2	M6	239	92	6	12	7.5	12.5	5	1.8	44	22	0.1030
30822-0300	3	M6	238	92	6	12	7.5	12.5	5	3.4	44	22	0.1030
30822-0400	4	M6	239	92	6	12	7.5	12.5	5	6.1	44	22	0.1030
30822-0500	5	M8	263	112	7	13	10	14.5	6	9.2	52	26	0.1840
30822-0600	6	M8	263	112	7	13	10	14.5	6	11.4	52	26	0.1840
30822-0600-10	6	M10	272	120	9	15	11	18	8	11.4	44	30	0.2980
30822-0800	8	M12	351	150	14	26	14	26	12	22.8	58	44	0.4240
30822-0800-10	8	M10	293	120	9	15	11	18	8	22.8	44	30	0.3930
30822-1000	10	M16	440	190	18	32	22	34	14	31.3	62	42	1.3540
30822-1200	12	M20	524	220	25	43	24	43	19	45	56	50	2.5660

NOTES

- The functionality is ensured only by using circular wire strand ropes of the 10820 and 10830 series.
- The screw-in depth of the threads must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.
- The user is responsible for independently verifying the correct installation and ensuring the appropriate rope diameter. Please refer to the instructions in the installation manual.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.