

TURNBUCKLE WITH CLEVIS SWAGED FOR ROPE Ø 2 - 12 MM

30870

TECHNICAL SPECIFICATION

Clevis with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 7 sizes, article no. 30870-0200 to 30870-1200.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30870
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	STATUS	Ø	A	B1	B2	E	F	G	H	Ø D	-	+	KG
30870-0200	Phased out	2	M5	178	80	6	12	7.5	12.5	5	34	26	0.0400
30870-0300	Phased out	3	M6	207	92	6	12	7.5	12.5	5	44	22	0.0700
30870-0400	Phased out	4	M6	211	92	6	12	7.5	12.5	5	44	22	0.0710
30870-0400-1	Phased out	4	M8	233	112	7	13	10	14.5	6	52	26	0.1360
30870-0800	Phased out	8	M12	355	150	14	26	14	26	12	70	34	0.4740
30870-1000	Phased out	10	M16	458	190	18	32	22	34	14	84	42	0.9940
30870-1200	Phased out	12	M20	554	220	23	43	24	43	19	98	50	1.8130

NOTES

- The screw-in depth of the threads must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.
- Suitable for the circular wire strand ropes of the 10820 and 10830 series.
- The assembly with open spiral strands of the 10810 series is only possible with diameters 2 - 6 mm.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.