

TURNBUCKLE WITH CLEVIS VISSLINE ROUND SWAGED

30870

TECHNICAL SPECIFICATION



828INDUSTRIES.COM

Jakob Rope Systems · Architectural Cables & Fittings

Clevis with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 7 sizes, article no. 30870-0400-15 to 30870-0800-15.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30870
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	STATUS	Ø	A	B1	B2	E	F	G	H	Ø D	WLL KN	-	+	KG
30870-0400-15	Phased out	4	M5	141	80	6	12	7.5	12.5	5	3.8	22	16	0.0380
30870-0400-16	Phased out	4	M5	162	80	6	12	7.5	12.5	5	3.8	34	26	0.0570
30870-0500-15	Phased out	5	M6	154	92	6	12	7.5	12.5	5	5.3	20	12	0.0770
30870-0500-16	Phased out	5	M6	181	92	6	12	7.5	12.5	5	5.3	44	22	0.0850
30870-0600-15	Phased out	6	M8	184	112	7	13	10.5	14.5	6	9.8	17	6	0.1500
30870-0600-16	Phased out	6	M8	216	112	7	13	10.5	14.5	6	9.8	51	26	0.1500
30870-0800-15	Phased out	8	M10	234	120	9	15	11	18	8	15	54	20	0.2830

NOTES

- Vissline thread-end with round shaft.
- Only in use with circular wire strand ropes of the 10820 series.
- The minimum free rope length between the fittings is 95 mm.
- The screw-in depth of the threads must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.