

TURNBUCKLE WITH EXTERNAL THREAD END SWAGED

30829

TECHNICAL SPECIFICATION

Turnbuckles assembled by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 15 sizes, article no. 30829-0200-01 to 30829-1600-01.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30829
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	Ø D	-	+	KG
30829-0200-01	2	M5	152	80	8	28	10	0.0280
30829-0200-02	2	M5	196	80	8	40	26	0.0350
30829-0300-01	3	M6	184	92	10	26	6	0.0550
30829-0300-02	3	M6	228	92	10	52	22	0.0650
30829-0400-01	4	M6	192	92	10	26	6	0.0600
30829-0400-02	4	M6	236	92	10	52	22	0.0700
30829-0400-03	4	M8	246	112	13.5	56	26	0.1310
30829-0500-01	5	M8	224	112	13.5	24	0	0.1050
30829-0500-02	5	M8	258	112	13.5	56	26	0.1280
30829-0600-01	6	M10	290	120	17.2	54	20	0.1880
30829-0600-02	6	M10	320	120	17.2	60	30	0.2170
30829-0800-01	8	M12	394	150	21.3	70	34	0.4200
30829-1000-01	10	M16	520	190	26.9	84	42	0.9330
30829-1200-01	12	M20	620	220	33.7	98	50	1.6270
30829-1600-01	16	M24	658	212	42	92	48	2.6700

NOTES

- The screw-in depth of the threads must be at least 1,5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the turnbuckle is to identify the left-hand thread.
- Suitable for the circular wire strand ropes of the 10820 and 10830 series.
- The assembly with open spiral strands of the 10810 series is only possible with diameters 2 - 6 mm.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.