

TURNBUCKLE WITH EXTERNAL THREAD END VISSLINE ROUND SWAGED

30829

TECHNICAL SPECIFICATION

Turnbuckles assembled by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 8 sizes, article no. 30829-0300-15 to 30829-0800-16.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30829
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	Ø D	-	+	KG
30829-0300-15	3	M4	85	45	7	14	8	0.0280
30829-0400-15	4	M5	134	80	8	22	15	0.0200
30829-0400-16	4	M5	164	80	8	40	25	0.0550
30829-0500-15	5	M6	146	92	10	20	12	0.0780
30829-0500-16	5	M6	176	92	10	50	22	0.0870
30829-0600-15	6	M8	172	112	13.5	17	6	0.1520
30829-0600-16	6	M8	212	112	13.5	57	26	0.1780
30829-0800-16	8	M10	220	120	17.2	54	20	0.2860

NOTES

- Only compatible with circular wire strand ropes of the 10820 series.
- The minimum free rope length between the fittings is 95 mm.
- The screw-in depth of the threads must be at least 1.5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the turnbuckle is to identify the left-hand thread.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.