TURNBUCKLE WITH EYE-END SWAGED

30889

TECHNICAL SPECIFICATION

828 CABLE SYSTEM INC.

828INDUSTRIES.COM

Jakob Rope Systems · Architectural Cables & Fittings

Eye-end with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 9 sizes, article no. 30889-0200 to 30889-1200.

SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30889
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	B3	E	H	K	Ø D	F_RD KN ETA	-	+	KG
30889-0200	2	M5	174	80	15	6	12	3	5.5	1.2	34	26	0.0350
30889-0300	3	M6	201	92	16	7	14	4	6.5	2.7	44	22	0.0630
30889-0400	4	M6	205	92	16	7	14	4	6.5	2.7	44	22	0.0650
30889-0400-01	4	M8	232	112	21	8.5	17	5	8.5	4.8	52	26	0.1300
30889-0500	5	M8	238	112	21	8.5	17	5	8.5	4.8	52	26	0.1290
30889-0600	6	M10	270	120	29	12	22	6	10.5	7.5	54	20	0.2210
30889-0800	8	M12	346	150	31	14	25	8	13	10.9	70	34	0.4100
30889-1000	10	M16	444	190	37	15	31	10	14.5	19.3	84	42	0.8420
30889-1200	12	M20	529	220	49	21	40	15	19.5	30.2	98	50	1.5100

NOTES

- The screw-in depth of the threads must be at least 1,5 times the thread diameter.
- (+) = extend (loosen)
- (-) = shorten (tighten)
- The marking on the shaft is to identify the left-hand thread.
- The design resistance FRd (kN) according to ETA refers to use with circular wire strand ropes of construction 6×19+WC (product group 10830). When using the 6×7+WC rope construction (product group 10820), the resistance value increases.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.