

TURNBUCKLE WITH EYE- END VISSLINE ROUND SWAGED

30889

TECHNICAL SPECIFICATION

Eye-end with turnbuckle swaged and self-assembly by Jakob Rope Systems, stainless steel AISI 316L (1.4404). 7 sizes, article no. 30889-0400-15 to 30889-0800-15.



SPECIFICATIONS

Brand	Jakob Rope Systems
Product no.	30889
Category	Architectural Cables & Fittings
Material	Stainless steel 316L

ARTICLE NUMBERS

NO.	Ø	A	B1	B2	B3	E	H	K	Ø D	F_RD KN ETA	-	+	KG
30889-0400-15	4	M5	138	80	15	6	12	3	5.5		18	10	0.0270
30889-0400-16	4	M5	158	80	15	6	12	3	5.5		34	26	0.0470
30889-0500-15	5	M6	148	92	16	7	14	4	6.5		20	12	0.0670
30889-0500-16	5	M6	175	92	16	7	14	4	6.5		44	22	0.0740
30889-0600-15	6	M8	183	112	21	8.5	17	5	8.5	12	17	6	0.1390
30889-0600-16	6	M8	200	112	21	8.5	17	5	8.5	12	51	26	0.1620
30889-0800-15	8	M10	235	120	29	12	22	6	10.5	24.1	54	20	0.2650

NOTES

- Vissline thread-end with round shaft.
- Designed for exclusive use with circular wire strand ropes of construction 6×7+WC (product group 10820).
- The minimum free rope length between fittings must be 95 mm.
- The screw-in depth of the thread must be at least 1.5 × the thread diameter.
- (+) = extend (loosen)
- (–) = shorten (tighten)
- The marking on the turnbuckle identifies the left-hand thread.

Specifications are provided for reference and may change without notice. Contact us to confirm the right product for your application.